

WSD 10



Hose designed for full suction and discharge pressure. Can handle sewage, waste water etc.

TECHNICAL CHARACTERISTICS

TUBE	Black SBR rubber tube
REINFORCEMENT	High tensile textile cord with helix steel wire
COVER	Black NR + SBR - abrasion - heat and weather resistant; Smooth wrapped inish.
TEMPERATURE	-20° C to +80° C
WORKING PRESSURE	10 Bar (150 PSI)

CODE	Inner Diameter ID		Outside Diameter OD		Working Pressure		Burst Pressure		Theoretical Weight
	mm	inch	mm	inch	bar	psi	bar	psi	Kg/m
92WS10025037	25	1"	37		10	150	30		0.94
92WS10032045	32	1 1/4"	45		10	150	30		1.25
92WS10038051	38	1 1/2"	51		10	150	30		1.56
92WS10045058	45	1 3/4"	58		10	150	30		1.80
92WS10051064	51	2"	64		10	150	30		2.01
92WS10064078	64	2 1/2"	78		10	150	30		2.61
92WS10076091	76	3"	91		10	150	30		3.16
92WS10089106	89	3 1/2"	106		10	150	30		4.56
92WS10102119	102	4"	119		10	150	30		5.16
92WS10127146	127	5"	146		10	150	30		6.92
92WS10152172	152	6"	172		10	150	30		8.36
92WS10203225	203	8"	225		10	150	30		12.71
92WS10254281	254	10"	281		10	150	30		20.89
92WS10304334	304	12"	334		10	150	30		29.14